

# WHEELS THAT WORK!

The WORX+ cup wheel range delivers exceptional performance hands down every time for every application.

## **TURBO RIM RANGE: FAST, AGGRESSIVE, SMOOTH!**



- An awesome cupwheel range with smooth results for hard to very hard concrete.
- Slightly more aggressive cut and scratch pattern than the REFINE range 60/80 and 100/120 grit are great for removing stubborn scratches.
- Will "stay open" longer when grinding, particularly when not using any floor treatment agent to keep them open.
- Premium edge grinding due to continual diamond perimeter with minimal "rounding" of outer edge of the cupwheel segment.
- Available in 30/40, 60/80 & 100/120 grit in 125mm (5") and 180mm (7").

### **FORCE RANGE: HIGH PRODUCTIVITY**



#### **FORCE RIP**

- A highly aggressive cup wheel range designed to deliver high productivity performance.
- · Choose for rapid removal of concrete, glues and thin film coatings from concrete and masonry surfaces.
- Available in125mm (5"),150mm (6") (to suit Hilti) & 180mm (7") diameters. 6mm segment height. 30/40 Grit. Soft & Medium bond.



#### **FORCE ARROW**

- With widely spread segments, the ARROW delivers optimal performance for coating removal without wheel clogging.
- · Choose for rapid removal of concrete, thick and thin film coatings from concrete and masonry surfaces.
- Available in 180mm (7") diameter. Soft bond.



#### **FORCE PCD**

- The Force PCD cup wheel makes removal of thick coatings fast and effective.
- Rip through coatings such as levelling compounds, mastics, epoxies and adhesives.
- Choose from two options: Fine smaller PCD pieces and coarse larger PCD pieces.
- Available in 125mm (5"), 150mm (6") (to suit Hilti) & 180mm (7") diameters.



- The choice for rapid and aggressive surface preparation.
- Available in 125mm (5"), 150mm (6") (to suit Hilti) and 180mm (7") diameter. 16/20 grit, 30/40 grit soft bond.

#### Excellent for:

- o The removal of thick roll down coatings, glues etc. where an aggressive high speed tool is required.
- o Medium to hard stock coating removal and the grinding/levellingof concrete.
- o Removal of thick coatings such as levelling compounds, mastics, epoxies, adhesives.
- o Grinding and levelling of concrete.

### **REFINE RANGE: THE ALL ROUNDER**

- Specifically designed for general purpose and finishing applications. An excellent all round tool with impressive performance capacity.
- Multi segmented for smooth operation where surface refinement is essential.
- Available in 125mm (5"), 150mm (6") (to suit Hilti) & 180mm (7") diameters.

8mm segment height 30/40, 60/80, 120/140 grit Soft & Medium bond



S.C.sannly

## TOTAL SOLUTIONS FOR CONCRETE GRINDING AND POLISHING CONTRACTORS



5/176 Canterbury Road, Bayswater Nth, 3153, Vic.

Tel: 1300 897 873 www.totallyworks.com

sales@totallyworks.com www.facebook.com/totallyworks

